



4100 TURBOLIGHT 10W-40

Gasoline and Diesel engine oil

Technosynthese®

TYPE OF USE

Technosynthese® lubricant specially designed for powerful and recent cars, powered by large displacement engine, turbo Diesel direct injection, or Gasoline engines with injection and catalytic converter.

Suitable for all type of fuels: leaded or unleaded Gasoline, ethanol, LPG and Diesel.
Compatible for catalytic converters.

PERFORMANCES

STANDARDS	ACEA A3 / B4 API SERVICES SM / CF
APPROVALS	MB-Approval 229.1 RENAULT RN0700 VW 501 01 / 505 00
PERFORMANCES	PSA B71 2300

The ACEA B4 performance requires an outstanding detergent/dispersant power and a better viscosity increase resistance due to soot produced by Direct Injection Diesel engines (except VW unit injector pump engines that require MOTUL SPECIFIC 505 01 502 00 505 00 5W-40).

The standard API SM is more stringent than API SL in terms of ageing resistance (average drain interval increased), requires anti-oxidation properties that maintain a constant viscosity avoiding sludge and deposits in the crankcase, anti-wear properties and dispersant power, and fuel economy benefits.

PSA for its B71 2300 norm requires oil to be able to endure the most severe thermal constrains in order to lubricate some of their Gasoline engines and some Diesel engines without DPF.

RENAULT has developed RN0700 standard for oils able to provide a high thermal stability and insure an outstanding resistance at high temperatures.

In general, RN0700 standard applies for all Naturally Aspirated Gasoline engines (except Renault Sport) of RENAULT Group (RENAULT, DACIA and SAMSUNG). The RN0700 standard applies also to all RENAULT vehicles fitted with Diesel engine 1.5 dCi without DPF < 100 HP with oil drain interval of 20 000 km or 1 year. Before use, always refer to the owner manual or handbook of the vehicle.

The reinforced synthetic base stock provides very high lubricating power which reduces frictions, decreases the volatility and ensures resistance to very high temperatures reached in modern engines. The viscosity grade SAE 10W-40 is fully suitable for recent Gasoline and Diesel engines. Anti-oxidation, Anti-wear, Anti-corrosion, Anti-foam properties.

RECOMMENDATIONS

Drain interval: according to manufacturers' recommendations and tune to your own use.
Can be mixed with synthetic or mineral oils.
Before use or if in doubt, always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	10W-40
Density at 20°C (68°F)	ASTM D1298	0.869
Viscosity at 40°C (104°F)	ASTM D445	101.9 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	14.8 mm ² /s
Viscosity Index	ASTM D2270	152
Pour point	ASTM D97	-36°C / -32.8°F
Flash point	ASTM D92	229°C / 444.2°F
TBN	ASTM D2896	10.1 mg KOH/g